

List of Claims:

1. (currently amended) A structure suitable for converting a non-touch screen display into a touch screen display for a computing device comprising:
 - a touch screen;
 - a casing;
 - the casing having an opening for the touch screen;
 - at least one casing surface;
 - a controller for the touch screen;
 - a computing device software driver for the touch screen;
 - a connection from the controller of the touch screen to the computing device,

whereby the casing is positioned over and substantially around the display for the computing device such that the touch screen in the casing opening is oriented directly over the display to convert a non-touch screen display to a touch screen display.
2. (original) The structure of claim 1 wherein the connection to the computing device is a Universal Serial Bus, Fire Wire, wireless, or cable connection.

3. (original) The structure of claim 1 wherein the casing further comprises at least one outer casing surface and at least one inner casing surface, whereby the at least one outer casing surface and the at least one inner casing surface define a space for the display to fit.

4. (original) The structure of claim 1 wherein the casing comprises a plastic composite.

5. (original) The structure of claim 1 wherein the casing further comprises at least one pivotable stand, which is positioned opposite to the opening of the casing, whereby the at least one stand supports the structure and the display.

6. (currently amended) A structure suitable for converting a non-touch screen display into a touch screen display for a computing device comprising:

a touch screen;

a casing;

the casing having an opening for the touch screen;

at least one casing surface;

a controller for the touch screen;

a computing device software driver for the touch screen;

Serial No. 10/679,930
Page 3 of 7

a connection from the controller of the touch screen to the computing device;

the casing surface having at least one pivotable stand;

whereby the casing is positioned over and substantially around the display for the computing device such that the touch screen in the casing opening is oriented directly over the display to convert a non-touch screen display to a touch screen display and whereby the at least one stand supports the casing and the display.

7. (original) The structure of claim 6 wherein the connection to the computing device is a Universal Serial Bus, Fire Wire, wireless, or cable connection.

8. (original) The structure of claim 6 wherein the casing further comprises at least one outer casing surface and at least one inner casing surface, whereby the at least one outer casing surface and the at least one inner casing surface define a space for the display to fit.

9. (original) The structure of claim 6 wherein the casing comprises a plastic composite.

Serial No. 10/679,930
Page 4 of 7

10. (currently amended) A method of using structure suitable for converting a non-touch screen display into a touch screen display for a computing device, said structure comprising a touch screen; a casing; the casing having an opening for the touch screen and at least one outer casing surface and at least one inner casing surface; the at least one outer casing surface and the at least one inner casing surface further defining a space for the display; a controller for the touch screen; a computing device software driver for the touch screen; a connection from the controller of the touch screen to the computing device, comprising the following steps:

Placing the casing over and substantially around the display into the space defined by the at least one outer casing surface and the at least one inner casing surface;

Installing the computing device software driver; and

Attaching the connection from the controller of the touch screen to the computing device,

Whereby the touch screen in the casing opening is oriented directly over the display to convert a non-touch screen display to a touch screen display.

11. (cancel).

Serial No. 10/679,930
Page 5 of 7

12. (original). The method of claim 10 further comprising moving a pivotable stand on the casing from a first closed position to a second opened position.

Serial No. 10/679,930
Page 6 of 7

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.